STATE OF OKLAHOMA CANADIAN COUNTY FILED OR RECORDED

NOV 1 2 2013

SHELLEY DICKERSON COUNTY CLERK 13815

# Six Month Bid



January 1, 2014 Thru June 30, 2014

APPROVED THIS 12th DAY OF Nov., 20 13.

PHIL CARSON, DISTRICT #1 COMMISSIONER

DAVID ANDERSON, DISTRICT, #2 COMMISSIONER

JACK STEWART, DISTRICT HE COMMISSIONER



# Canadian County Purchasing

## Six Month Bids January 1 – June 30, 2014

Date Issued: Bid Number: November 12, 2013 **SIX MONTH BIDS** 

Closing Date:

December 6, 2013 at 4:00pm

PO Box 458, 201 N. Choctaw Ave., El Reno, OK 73036

Opening Date:

December 9, 2013 at 9:30am

Commissioner's Meeting Room, 201 N. Choctaw Ave., El Reno, OK 73036

#### ~ NOTICE TO BIDDERS~

Sealed bids will be received by the Canadian County Purchasing Agent of Canadian County, Oklahoma at the Court House in El Reno until 4:00pm on the 6<sup>th</sup> day of December, 2013. Bids will open at 9:30am on the 9<sup>th</sup> day of December, 2013.

Bids will be opened by the Board of Canadian County Commissioners on that date for the six month period of:

January 1, 2014 through June 30, 2014

All bids must be made on forms furnished by the County, signed and notarized and shall conform to the regulations and conditions contained herein.

The Canadian County Board of County Commissioners reserves the right to reject any all bids or to award all or any portion of the items bid.

#### Please mail sealed bids to:

Sherry Murray, Purchasing Agent Canadian County Clerk's Office PO Box 458 El Reno, OK 73036

Street Address: 201 N. Choctaw Avenue, El Reno, OK 73036

Please mark your envelope "Six Month Bid"

Sherry Murray, Purchasing Agent
Canadian County Clerk's Office
PO Box 458
El Reno, OK 73036


SIX MONTH BID

Closes: December 6, 2013 at 4:00pm

If you have any questions or need additional information, please contact: **Sherry Murray**, Purchasing Agent, 405.295.6125 or 405.422.2441



~TABLE OF CONTENTS~	PAGE:
Bid Regulations and Conditions	4
Bid Contents	
Vendor Performance	
Affidavit of Non-Collusion	
Asphalt Reclaiming	14
Asphaltic Materials	23
Bituminous Seal Coat	18
Bleed Control Emulsion	19
Bridge Construction	11
Bridge Planks	12
Chicken – For Jail	19
Cold Milling Asphalt	14
Concrete – Furnished and Unloaded	13-14
Corr. HDPE Pipe	11
Corr. Metal Arched Pipe (See State Contract)	S/C
Corr. Culvert Pipe (See State Contract)	
Delineator Posts – Flexible	11
Dry Calcium Chloride	21
Dry Magnesium Chloride	21
End Wings	10
End Wings-Round Corr. (See State Contract)	
End Wings-Metal Arched Pipe (See State Contract)	
Fir (ACZ)	9
Forming-Stay in Place	9
Ground Beef – For Jail	19
Guard Rail – Galvanized	10



~TABLE OF CONTENTS~  GYP – Processed	25
H-Piling	
Hauling of Rip Rap	
Hauling of Rock	
Hot Mix Asphalt	
Hot Mix Hauled in place 700-1400 tons	
Hot Mix Hauled in place over 1400 tons	
Kiln Dust	
Liquid Calcium Chloride	
Magnesium Chloride	
Material Costs – Delivered for Kiln Dust	
Oil and Chipping	
Pavement Line Striping	
Pipe Piling – New	
Pipe Piling – Used	
Prime Oil Application	
Railroad Flat Cars	
Railroad Tank Cars	
Rental of Equipment	
Road Rock	
Rock – Picked up by County	
Shale – Processed	
Steel Pipe – Used	
Steel Sheet Piling – Interlocking	
Structural Steel	
Weed Spraying	

#### ~BID REGULATIONS AND CONDITIONS~

#### **BIDDERS LIST:**

- A. Vendors wishing to do business with the County should be included on the "Bidders List" maintained by the County Purchasing Agent. All vendors are eligible for consideration.
- B. Vendors wishing to be added to the "Bidders List" should contact the County Purchasing Office.
- C. Removal from the "Bidders List".
  - 1. <u>Removal or Suspension</u>. The Purchasing Agent may remove any vendor on the Bidders List for such period of time deemed necessary by the Purchasing Agent.
  - 2. <u>Cause for Removal or Suspension</u>. The following shall be deemed sufficient grounds for removal or suspension:
    - a) Three consecutive failures to respond to the Notice to Bidders.
    - b) Failure to submit certificate of compliance when required.
    - c) Consistent failure to conform to bid regulations, conditions, and/or specifications.
    - d) Failure to make timely deliveries.
    - e) Failure to keep bid firm for the time specified on the Notice of Bid.
    - f) Collusion with other bidders or prospective bidders to restrain competitive bidding.
    - g) Bankruptcy or other evidence of insolvency of the bidder.
    - h) Giving false or misleading information in an application for inclusion of the "Bidders List".
    - i) Any violation of these rules and regulations or other information suggesting that the bidder is no longer responsible and qualified to do business with the County.
  - 3. <u>Notice of removal or suspension</u> from the Bidders List will be sent to affected vendor. This action may be contested in writing to the Purchasing Agent within five working days.

#### **BIDDING PROCEDURES:**

#### A. Solicitation of Bids.

- 1. <u>Concerning Solicitation</u>. The Purchasing Agent provides fair and impartial consideration to all qualified bidders and seeks to obtain the highest practicable degree of full and free competition. All interested vendors are urged to apply for inclusion on the Bidders List.
- 2. <u>Bid Selection</u>. The County Commissioners may reject any or all bids. The Purchasing Agent will solicit phone bids from three or more vendors selected at random, if this occurs.

#### B. Bid Form:

- 1. Bids are submitted on the forms containing items and/or goods a vendor wished to bid. Return of bid constitutes a valid offer good for 30 days from the date of opening.
- 2. Formal Requirements.
  - a) Written in Ink or Typewritten. All bids must be written legibly in ink or preferably typewritten.
  - b) Authorized Signature. The bid must bear the signature in ink by the person so authorized.
  - c) Notary Seal. Each bid <u>must</u> bear the signature and seal of an authorized Notary Public on the Affidavit of Non-Collusion.
  - d) Labeled and sealed envelope. Bidders name and address and closing date must appear on the face of the envelope.



#### HOLD HARMLESS AGREEMENT:

All bidders shall defend, indemnify and hold the County of Canadian County, State of Oklahoma, its commissioners, officers, deputies and employees harmless from and against any and all liability, loss, expense (including reasonable attorney's fees), or claims for injury or damages arising from, relating to, or connected with the performance of the bidding work.

#### **BID CONTENTS:**

- 1. Entire Agreement. The Bid Regulations and Conditions of this section together with the Notice of Bid and any other sheets or documents made a part of the bid package, shall constitute the entire agreement between parties.
- 2. Modification. An addendum will be issued, when deemed necessary, for any changes in, additions to, or waivers of specifications, or regulations and conditions of the bid. The Purchasing Agent must issue this addendum.
- 3. Offer firm for thirty days. Return of bid constitutes a valid offer guaranteed for a minimum of 30 days by vendor until bid is awarded. After bid is awarded offer is firm for six months.
- 4. Items to be new or current. Unless otherwise stated within the bid, goods and materials offered in the bid are to be new and of current design.
- 5. Non-Acceptance of Split Award "All or None Bid" The County Commissioners reserve the right to make and award on items or groups of items listed on the bid. If the vendor wishes to bid "All or None", this must be clearly shown of the bid.
- 6. Shipping Instructions. Goods and materials are to be shipped F.O.B., the receiving officer or department. All freight is to be borne by the vendor and included in the bid price.
- 7. Title and Risk of Loss. Title of goods shall not pass from the vendor until such goods are received by requisitioning departments receiving officer. Risk of such loss prior to such receipt shall be borne by the vendor.
- 8. Delivery. Time is of the essence and deliveries are to be made within ten days after receipt of an order. Items to be picked up by the County shall be ready within 24 hours of notice.
- 9. Inspection and Rejection. All goods and materials shall be subject to inspection by the receiving officer at the time of delivery. Any goods not in complete conformance with the specifications, defective in materials of workmanship, or found to contain latent defects will be rejected. Such goods are to be removed and replaced by and at the cost of the vendor promptly after notifications of rejection. Risk or loss as to such rejected goods shall be borne by the vendor.
- 10. Payment. Payment by the County for goods received shall not constitute acceptance if subsequent reveals latent defects or a failure to meet bid specifications. Payment for a period delivery shall not be deemed acceptance of undelivered goods.
- 11. Exemption from Taxes. Purchases made by the County are exempt from State Sales Tax and from Federal Excise Tax. These taxes should not be included in bid prices. When required, the Purchasing Agent will supply the proper tax exemption certificate.

#### SUBMISSION PROCEDURES:

- A. Sealed envelopes. Bids must be submitted in a sealed envelope with the name and address of the vendor and date and time of closing clearly marked on the outside of the envelope.
- B. Late Bids. Bids received after the time and date of closing listed on Notice to Bidders will not be opened. These late bids will remain unopened and become a permanent part of the bid file.



#### **AWARDING OF BIDS:**

A. Acceptance. The Purchasing Agent will compile the bids submitted. The County Commissioners will open and award all bids. The Purchasing Agent will notify all successful bidders in writing prior to onset of the bidding period.

Purchases of items and supplies that are on this Six Month Bid list must be made from the vendor listed. This is an exclusive contract between Canadian County and the vendor for the time period mentioned on the "NOTICE TO BIDDERS". The county must be as sincere in fulfilling its obligation by buying from the vendor as it expects the vendor to be in holding the price stable to the bid period.

- B. Grounds for Rejection:
  - 1. Non-Responsive Bid. Any bid which does not meet the requirements or specifications of the bid, or is unsuitable for the intended use, or does not comply with these regulations and conditions may be rejected. The County Commissioners reserve the right to reject any or all bids when such is deemed in the best interest of the County.
  - 2. Affidavit. The Non-Collusion Affidavit not signed and notarized and/or included with the bid.

#### PERFORMANCE BY SUCCESSFUL BIDDER:

- A. Delivery of Goods:
  - 1. Deliveries shall be made within ten days from the date ordered. Items to be picked up by the County shall be ready within 24 hours of Notice.
  - 2. Deliveries are to be made to the requisitioning department and the vendor will be advised of such time of order.

#### **SPECIAL CONDITIONS FOR ROAD MATERIALS:**

- A. The County Commissioners request that all hauling orders be started within 48 hours after receipt of order of hauling. This includes verbal request supported by a valid Purchase Order No. and minimum of (6) trucks are to be assigned to a specific project unless otherwise agreed to. If low bidder cannot accommodate, the county may proceed to next bidder. All boundary line hauling will be paid the lower bid price for that area.
- B. All materials must meet current ODOT Specifications. A materials certification attesting to the specification regarding delivered material may be requested. Any material found to be in noncompliance (not meeting required specifications) will not be paid for or a cost reduction may be applied at the county's discretion.
- C. Bidder agrees to deliver asphaltic materials in truck tank lots within 24 hours notice from the County Purchasing Office. THE MATERIAL SHALL BE MAINTAINED AT SATISFACTORY TEMPERATURE UNTIL IT IS LOADED INTO THE COUNTY EQUIPMENT. DEMURRAGE OR DELIVERY CHARGES WILL BE ALLOWED IN CASES OF DELAY OR FAILURE OF THE COUNTY TO ACCEPT THE MATERIALS BECAUSE OF BREAK DOWN OF COUNTY EQUIPMENT WEATHER CONDITIONS. PLACE OF COUNTY DELIVERY SHALL BE LISTED ON THE INVOICE. FAILURE BY THE VENDOR/SUPPLIER TO DELIVER MATERIALS AT THE PROPER TIME AND PLACE AS ORDERED BY THE COUNTY CAN RESULT IN LOSS OF TIME CHARGE AFFECTED BY THE COUNTY ON THE SUPPLIER.
- D. CANADIAN COUNTY WILL NOT BE RESPONSIBLE FOR, AND WILL NOT PAY FOR ANY FUEL SURCHARGES, EMERGENCY OR OTHERWISE. THIS WILL BE PAID BY THE VENDOR OR CARRIER AND WILL NOT BE PASSED ON TO THE COUNTY FOR PAYMENT.

#### **SUB-LETTING:**

A. Any bid submitted with sub-letting to firm other than the bidding vendor will or shall be CLEARLY SPECIFIED ON THE BID SHEET.



#### THE USE OF RECYCLED MATERIALS:

A. If a vendor has products using recyclable materials and regular materials, the vendor shall submit separate bids, using one bid for recyclable materials only and using one bid for regular materials.

#### **CHANGING OF BID SPECIFICATIONS:**

A. Bid forms shall be filled out as specified. If a Vendor chooses to change the bid specifications, the bid will be subject to rejection by the Board of Canadian County Commissioners.

#### **ALUMINIZED STEEL TYPE "2" PIPE SPECIFICATIONS:**

A. This proposal for furnishing Corrugated Aluminized Steel Type "2" Pipe as per Oklahoma State Highway Specifications, Section 726, 1999 Edition and Supplements, delivered F.O.B. to specified locations in Canadian County. Steel Sheet, aluminum-coated (type 2) by the hot-dip process for sewer and drainage pipe shall conform to the AASHTO M 274.



AFFIDAVIT MUST BE INCLUDED WITH YOUR BID OR BID WILL BE REJECTED BY THE BOARD OF CANADIAN COUNTY COMMISSIONERS.

#### RETURN THIS PAGE WITH THE BID.

#### ~AFFIDAVIT OF NON-COLLUSION OF BIDS~

STATE OF
COUNTY OF
I, the undersigned of lawful age, being first duly sworn on oath say that he or she is the agent authorized by the bidder to submit the attached bid. Affidavit further states that the bidder has not been a party to any collusion among bidders in restraint of freedom of competition by agreement to bid at a fixed price or to refrain from bidding; or with any state official or contract, or in any discussions between bidders and any state official concerning exchange of money or other things of value for special consideration in letting of a contract, that the bidder/contractor has not paid, given or donated or agreed to pay, give or donate to any officer or employee of the State of Oklahoma or other public entity thereof, any money or other thing of value, either directly or indirectly in the procuring of the award of a contract pursuant to this bid.
BUSINESS NAME:
ADDRESS:
PHONE NUMBER:FAX NUMBER:
SIGNATURE:
TITLE:
(NOTARIZATION)
SUBSCRIBED AND SWORN BEFORE ME THISDAY OF, 20
(NOTARY PUBLIC) (COMMISSION EXPIRATION DATE)
(SEAL)



## RETURN ONLY THE PAGES THAT YOU HAVE BID ON

DATE:			100	_				
NAME O	F FIRM:			_				
	ВІ	DDER AGREE	S TO COMPLY	WITH ALL TER	MS AND CO	NDITIONS	OF BID	
SIZE:	LENGTH:	ACZA FIR	(price per thousa	and feet) SIZE	: LENGTH:	Southern	Yellow Pine – C	
3" x 4"	8' to 16' 18' to 24'			3" x	4" 8' to 16' 18" to 24'		·····	<u>Treated</u>
3" x 6"	8' to 16' 18' to 24'			3" x	6" 8' to 16' 18' to 24'			
3" x 8"	8' to 16' 18' to 24'			3" x	8" 8' to 16' 18' to 24'			
3" x 12"	8' to 16' 18' to 24'			3" x	12" 8' to 16' 18' to 24'			
4" x 12"	8' to 16' 18' to 24'			4" x	12" 8' to 16' 18' to 24'			
4" x 14"	18' to 20' 22' to 24'			4" x	14" 18' to 20' 22' to 24'		<del></del>	
8" x 16"	20' to 30' 32' to 40'			8" x	16" 20' to 30' 32' to 40'			
12" x 12"	8' to 16' 18' to 20' 22' to 26'			12"x	12" 8' to 16' 18' to 20' 22' to 26'			
BETTER DRESSIN	LUMBER AI	ND SHALL BE	DOUGLAS FIR CHEMONITE (A IBER SHALL CO 88 EDITION.	ACZA) TREATE	D WITH .40	TREATMEN	IT RETENTION	I. LUMBER
	THERN YEI MENT SPECI		rreated with	H #1 CREOSO	TE PER AV	WPA AND	OKLAHOMA	HIGHWAY
GAUGE: 22 gauge_		OR TENSEL FO	<b>DRM:</b> price per so	quare foot: (New p	orime materia	l: PAINTEC	<b>)</b> )	
RESPECT	FULLY SUB	MITTED BY:						



# RETURN ONLY THE PAGES THAT YOU HAVE BID ON BID PROPOSAL CANADIAN COUNTY

DATE:	CANADIAN COUNT I
	BIDDER AGREES TO COMPLY WITH ALL TERMS AND CONDITIONS OF BID
	G: outside diameter – price per foot:
.50 (1/2) wall thickne	PSS PSS
7" 7.5.69	<del>_</del>
7 5/8" 9 5/8"	
9 3/8 10 <sup>3</sup> / <sub>4</sub> "	<del>_</del>
12"	
14"	<del></del>
	G: outside diameter – price per foot:
.50 (1/2) wall thickne 7"	SS SS
7 5/8"	<del></del>
	<del></del>
10 %" 12"	<del>-</del>
14"	<del>_</del>
<u>GALVANIZED GU</u>	ARD RAILS: (NEW) per 12.6 ft. section: per 25 ft. section.
	(USED) <u>per 12.6 ft. section:</u> <u>per 25 ft. section.</u>
GALVANIZED GU	ARD RAILS: Installed price per L.F.
(As per ODOT 2009	Standard Specifications Section 623 – See Attachment Exhibit "A")
(115 per ODO 1 200)	Standard Specifications Section 025 – See Attachment Exhibit A
END WING: (NEW	price for each. (USED)price for each.
	· · · · · · · · · · · · · · · · · · ·
	EEL: NEW price per pound for angles, channels and flats (A 36 GRADE OR BETTER – bid will not
include re-bar or an	vy steel 3" dimension or less)
	USED <u>price per pound</u>
	NEW price per pound for 6" to 24" wide flange beams  NEW price per pound for 27" to 36" wide flange beams
10 x 10 x 42 # H-PII	
NEW:	Arto.
<u>USED STEEL PIPE</u>	
thickness: price per fe	pot:
16"	
18"	
20"	
22" 24"	
RESPECTFULLY SI	UBMITTED BY:



#### RETURN ONLY THE PAGES THAT YOU HAVE BID ON

DATE:					****	CAIV	ADIAN C	OUNT	1				
NAME OF	FIRM:												
		BIDDE	ER AC	GREES T	о сом	PLY W	ITH AL	L TERM	MS AND	COND	ITIONS OF BII	)	
CORRUGA (AASHTO M	TED HI	OPE PIPE	(High	Density P	olyethyle	ne AASI	HTO M25	2 / M294	Specifica	ıtion) — 1	0', 20', 24' or 30'	Lengths	
4"	LF	8"	_LF	10"	LF	12"	LF	15"	LF	18"	LF 24"	LF	
30"	LF 3	36"	LF	42"	LF	48"	LF	60"	LF				
(Coupler) 4"	EA	8"	_EA	10"	EA	12"	EA	15"	EA	18"	EA 24"_	EA	
30"	EA 3	36"	EA	42"	EA	48"	EA	60"	EA				
Delivery lead Dual Wall H under roadwa	IDPE qu	uoted as A	LT to	Corrugated	i Metal P	ipe adver	tised. All					d M294 or M252 fo	or us
7 gauge	DELIN	ACK) (1 — — — — — — EATOR P	8" GA	LVANIZE : price per	D)	<u>(21.7" E</u>	oot: BLACK)  	(21 ————————————————————————————————————	.7" GALV	'ANIZEI	<u>))</u>		
4" x 62" 4" x 72" BRIDGE CO		_	reneed	or sneeting	s on top)								
(DISTRICT: (This will be Crane with p Does this inc Welding Uni Does this inc Welder Help VENDOR SI SUPPLY A F	#1 ONL awarded ile-drive lude trave t and Op lude trave er: price HALL S PERFOR	Y) I to the con r and opera vel time? terator to de vel time? per hour: _ UPPLY GI RMANCE I	o bridg	ice/hour tr  ge construc  Forklif AL LIABI	avel time tion: price t: price pe	not inclue/hour tra	vel time no	ot includ			CE VERIFICATIO	DN, AND SHALL A	ALS(
BRIDGE CO (DISTRICT	<u>ONSTRI</u> #1 ONI	<u>UCTION:</u> LY) Trackl	hoe wi	th operator	r: price/ho	our travel	time not i	ncluded:					
RESPECTFU	JLLY S	UBMITTE	D BY										



RESPECTFULLY SUBMITTED BY:

### Six Month Bids January 1 – June 30, 2014

RETURN ONLY THE PAGES THAT YOU HAVE BID ON **BID PROPOSAL CANADIAN COUNTY** DATE: NAME OF FIRM: BIDDER AGREES TO COMPLY WITH ALL TERMS AND CONDITIONS OF BID **GALVANIZED BRIDGE PLANKS: 6X2 (LAYS 24"):** WEIGHT PER PRICE PER **GAUGE** SQ. FOOT: SQ. FOOT: 12 6.2# 10 8.0# 7 10.7# **BLACK BRIDGE PLANKS: 6x2 (LAYS 24"):** 12 6.0# 10 7.14# 7 10.5# ALL GAUGES AVAILABLE IN BLACK OR HOT-DIPPED GALVANIZED STEEL. GAUGE 10-12: ASTM DESIGNATED a446 GRADE B, ZINC COATED TO CLASS G210 PER ASTM DESIGNATED A525.GAUGE 7: ASTM DESIGNATED A570 GRADE 36, ZINC COATED TO ASTM DESIGNATED A123 EXCEPT THAT THE ZINC SHALL BE APPLIED AT A RATE OF 2.0 OZ./SQ/FT. TOTAL BOTH SIDES. **HAULING OF ROCK - END DUMP TRAILER - PRICE PER LOADED MILE:** \$ \_\_\_\_\_ FROM RICHARD SPUR: \$ FROM CYRIL: FROM COOPERTON: FROM GREENFIELD: \$\_\_\_\_ FROM HYDRO: \$ FROM DAVIS: \$\_\_\_\_\_ FROM MILL CREEK: \$\_\_\_\_ FROM CARNEGIE: FROM GRANITE: FROM WATONGA: \$ HAULING OF ROCK - BELLY DUMP TRAILER - PRICE PER LOADED MILE: FROM RICHARD SPUR: \$ FROM CYRIL: \$\_\_\_\_ FROM COOPERTON: FROM GREENFIELD: \$ FROM HYDRO: \$\_\_\_\_\_ FROM DAVIS: \$ FROM MILL CREEK: \$ FROM GRANITE: FROM CARNEGIE: FROM WATONGA: \$ ATTENTION VENDOR: FOR ALL THE ABOVE HAULING LIST NUMBER OF BELLY AND END DUMP TRAILERS THAT ARE AVAILABLE: **BELLY END** THIS MAY DETERMINE BID AWARD. (MUST HAVE A MINIMUM OF (6) SIX TRUCKS)



### RETURN ONLY THE PAGES THAT YOU HAVE BID ON

DATE:	· · · · · · · · · · · · · · · · · · ·			CANADI. 	AN COU	NTY		
NAME OF FIRM:								
ви	DDER AGR	EES TO	COMPL	Y WITH	I ALL T	ERMS AND CO	NDITIONS (	)F BID
HAULING OF ALL SIZ	ZES OF RII	PRAP: E	ND DUN	ИР; PRI	CE PER	LOADED MILE	<u>:</u>	
FROM RICHARD SPUR	k: \$	FROM	CYRIL:	5	S	FROM CO	OPERTON:	\$
FROM GREENFIELD:	\$	FROM	HYDRO	): §	S	FROM DA	VIS:	\$
FROM GRANITE:	\$	FROM	MILL C	REEK: \$	3	FROM WE	EATHERFOR	D:\$
FROM SOUTHARD:	\$	FROM	WATO	NGA:	\$	_ FROM OK	ARCHE:	\$
ATTENTION VENDOI ARE AVAILABLE: THIS MAY DETERMI	BELI END	LY	AP HAU	LING LI	<u>ST NUM</u>	IBER OF BELL	Y AND END	DUMP TRAILE
<ul><li>PRIME OIL APPLICA</li><li>1) Vendor will furnish ed labor and oil.</li><li>2) Vendor will furnish ed</li></ul>	quipment, quipment and		\$_			20'ROADWAY \$ \$	\$	ADWAY
labor. County will fur VENDOR TO FURNISI		CONTI	<u>ROL</u>					
CONCRETE: FURNISH		NLOAD	ED; PRIC	CE PER C	UBIC Y	ARD: (All curre	ent ODOT sp	ecifications apply
water/cement and air co PSI STRENGTHS: 250 GEARY: OKARCHE:	00 3000 — —		4000		igh Early	_		
PIEDMONT: CALUMET:						<del>-</del> - -		
EL RENO: YUKON: MAPLE:						_		
WALNUT: UNION CITY:						- - -		
VENDOR'S PRICE PER WHEN DOES HOLDING IS THERE A MINIMUM							YES NO	
WHAT IS THE MINIMU							110	
RESPECTFULLY SUBN	IITTED BY	:						



# RETURN ONLY THE PAGES THAT YOU HAVE BID ON BID PROPOSAL

DATE:		CANADIAN C	JOINT T	
	BIDDER AGR	EES TO COMPLY WITH AL	L TERMS AND CONDITIONS OF BI	D
VENDORS BII	ME FOR DELIVERY DDING ON CONCRE	ONCE ORDER IS PLACED? _ ETE SHALL USE THE ENCLO LISTED WILL BE USED IN TH	SED TRUCKING DISTRICT MAPS FO	OR EACH LOCATION.
INSURANCE:	SUCCESSFUL BID	DER WILL BE REQUIRED	TO PROVIDE ASSURANCE TO IND	EMNIFY AND SAVE
HARMLESS 1	THE COUNTY FRO	OM ANY LIABILITY OR DA OF TRANSPORTING.	MAGE TO PRIVATE OR PUBLIC F	PROPERTY OF LIFE
Vendor to furning to furning to form to furning to furn	ish equipment and oper each job required by MG ASPHALT: price ish equipment and oper	erator. Awarded vendor will ne the County Commissioner.	th:6" to 9"depth:  red to furnish proof of liability insurance  all depth: (County will haul)  red to furnish proof of liability insurance	
<b>RAILROAD T</b> INCLUDE DEI Pl	TANK CARS WITH T LIVERY. RICE PER FOOT:	THE ENDS REMOVED-TANK  6' 7' 8' 9'	CARS SHALL BE READY TO INSTA 6' 6"	ALL. PRICE SHOULD
RAILROAD F	LATCARS: PRICE F	PER FOOT: 8'	10'	
10' DIAMETE	R 1/2 TANK DELIV	<b>ERED</b> WITH MINIMUM 15" V	WIDE CHANNEL IRON FOOTERS, MI	NIMUM 3/4"THICK.
PRODUCT And AREA: KILN DUST: Geary Okarche Piedmont Calumet El Reno Yukon Maple Walnut Union City Mustang			OVER 10,000 SQ. YDS. (Application & Stabilization)	
RESPECTFUL	LY SUBMITTED BY	<del>:</del>		



### RETURN ONLY THE PAGES THAT YOU HAVE BID ON

## BID PROPOSAL

DATE:
NAME OF FIRM:
BIDDER AGREES TO COMPLY WITH ALL TERMS AND CONDITIONS OF BID
SPECIFICATIONS FOR SUBGRADE MODIFICATION: DESCRIPTION: This work shall consist of constructing one or more courses of a mixture of soil, fly ash, lime or cement kiln dust as required and water, in accordance with these specifications and in reasonably close conformity with the lines, grades and typical cross sections shown on the Plans or established by the Engineer.
MATERIALS: Materials shall meet the requirements specified in the following Sections and Subsections of Section 700-Materials CEMENT KILN DUST  AS PER SPECIFICATIONS
DELIVERED MATERIAL COSTS: Delivered cost to any designated area in the following delivery zones. The total delivered cost shall include the cost of the material all applicable hauling costs including but not limited to, dump or spread fees, fuel surcharges, loading, unloading and or weighing costs. Use trucking district map enclosed for detail on zone area.
Notice required by vendor prior to delivery:hours  We agree to deliver within a 2 hour time window of the specified delivery time. YESNO  List any exceptions to specifications:
Material Manufacturer:  Location:  Dealer Name: Contact Person:
MATERIAL: Cement Kiln Dust for soil stabilization: The cement kiln dust is to be used for soil stabilization in lieu of lime or fly ash: Cement Kiln Dust is required to meet the following chemical composition: S102 14.30% AL203 3.50% Fe203 1.79% CaO 48.46% MgO 1.65% SO3 4.25% Na20 0.32% K2O 3.08% LOI 20%
The material should have a free lime content of 8 to 10% with a bulk density of 70 to 80lbs. a cubic foot. The material should be free of clumps or partially set CKD. Material that has become wet or partially set will not be accepted for payment and will be removed from the roadway at the cost of the vendor. The material should be delivered in closed or tarped trucks to the jobsite. The vendor is advised that timely delivery will be required. The successful bidder may be required to deliver as many as ten loads per day, all within a two hour time window. Untimely delivery will be considered grounds for revocation of this bid contract.
EQUIPMENT: GENERAL: All earthwork equipment necessary for construction of stabilized sub-grade shall be in good operating condition, and equipped with all safety equipment required by law. The following equipment is subject to the specifications below and furnished in accordance with the requirements of the contract.
TRAVELING PLANTS: Traveling plants used for asphalt pulverization and soil mixing shall be equipped with carbide teeth and shall be capable of mixing up to one foot in depth in a single pass.
RESPECTFULLY SUBMITTED BY:
201 N. Choctaw Avenue, El Reno, OK 73036



#### BIDDER AGREES TO COMPLY WITH ALL TERMS AND CONDITIONS OF BID

**COMPACTORS:** Equipment for compaction shall meet the requirements of section 301 subsection C2 and C3 (ODOT Standard Specifications, 1988 Edition) with the following additions. The soil compactor shall be vibratory and have a minimum drum width of 84 inches. The contractor shall also have a self-propelled pneumatic roller, not less than 5 tons in weight that covers a rolling width of 60 inches.

<u>WATERING EQUIPMENT:</u> Water trucks or water wagons will have positive and rapidly working valves and a pressurized water spray system that delivers the water in a uniform spray pattern. <u>Gravity feed water systems will not be allowed.</u>

#### **CONSTRUCTION METHODS:**

GENERAL: It is the primary requirement of these specifications to secure a completed course or courses of sub-grade materials containing a uniform mixture of the stabilization additive required, with uniform density and moisture content, free from loose or segregated area and well bound for its full depth with a smooth surface suitable for placing subsequent courses. It shall be the responsibility of the contractor to regulate the sequence of his work, to use the prescribed amount of stabilization additive, to maintain the work and re-work the courses as necessary to meet the above requirements.

<u>WEATHER LIMITATIONS</u>: Stabilization operations shall not be performed when the sub-grade is frozen or when the air temperature in the shade is less than 40 degrees F. The contractor shall be responsible for the protection and quality of the modified sub-grade mixture under any weather conditions.

**PREPARATION OF EXISTING ROADBED**: Prior to stabilization, the roadbed shall be thoroughly pulverized to the point that all the processed and broken asphalt will pass a 3-inch sieve. Except by special permission from the Engineer, the length of roadway that may be pulverized at any time shall not exceed the length in which stabilization and compaction can be completed in two calendar days. The road bed will then be shaped and graded to be in reasonably close in conformity with the typical section, lines and grades as shown on the plans or as established by the Engineer. The contractor may be required to proof roll the sub-grade and to correct any soft areas that this rolling may reveal.

SCARIFYING AND LOOSENING: In some instances, scarifying and loosening may be required prior to stabilization to achieve the desired results as determined by the Engineer. Precautions shall be taken to avoid forming furrows of loosened material below the depth specified for the bottom of the modified sub-grade. Except by special permission from the Engineer, the length of roadway scarified and loosened at any time shall not exceed the length in which mixing compaction can be completed in two calendar days. In sub-grade extents designated on the Plans or by the Engineer as having excessive rock, the dimensions or quantities of which 25 percent or more are greater than 2.5 inches in size makes compliance with these specifications impractical, the Engineer may waive certain portions of the work as described below. The Engineer may require exploratory scarifying by the Contractor before designation of extents for which full compliance of these specifications is waived.

APPLICATION OF STABILIZATION MATERIALS: The proportion of the material indicated on the plans is approximate. The material shall be applied at the rate prescribed by the Engineer based on tests of the sub grade soil. Equipment necessary for proper control of the application rate shall be provided by the Contractor. Where tests indicate a significant change in the sub-grade soil, the Engineer will establish a new rate as deemed necessary for the section of road affected and prescribe a new application rate. Dry methods of application shall be utilized for placement of the cement kiln dust and fly ash onto the sub grade. Equipment for spreading shall be approved types which demonstrate the ability to distribute the material uniformly. Stabilization shall not be attempted when wind conditions are such that blowing dust becomes objectionable to traffic or adjacent property owners. Materials shall be placed only on that area of roadway where mixing, compaction and finishing can be completed in the same day. (Initial Mixing for lime) During the interval of time between application and completion of the first mixing operations, fly ash or cement kiln dust that has been exposed to weather conditions resulting in excessive wetting or excessive loss by blowing will not be accepted for payment. Stabilization material unacceptable as the result of wetting shall be removed from the roadway at the direction of the Engineer.

#### **MIXING:**

**GENERAL:** Spreading and mixing of fly ash or cement kiln dust material and the sub-grade soil shall be a continuous construction operation. The work area for a single traveling plant shall not exceed 4,000 square yards per day unless otherwise authorized by the Engineer.



#### BIDDER AGREES TO COMPLY WITH ALL TERMS AND CONDITIONS OF BID

FIRST MIXING: The moisture content of the sub-grade soil shall not exceed 80 percent of the optimum as determined as AASHTO T 99 at the time of first mixing. The soil and stabilization additive shall be mixed until a uniform mixture is obtained in which all clods and non-aggregate lumps are reduced to a maximum of 2.5 inch diameter size. The addition of water will not be permitted during the first mixing. First mixing operations shall begin no later than four hours after application of the additive. When deemed necessary by the Engineer, any portion of the work area shall be rescarified and additional material added to ensure adequate soil modification.

<u>CURING PERIOD</u>: There will be a mandatory curing period of 48 hours when lime is used for stabilization. The sub-grade will be kept damp during the curing period and free of ruts or depressions that hold any excessive water on the sub-grade. There will be no curing period or delay allowed between the first and final mixing of fly ash or cement kiln dust, these products must be installed in a continuous operation.

FINAL MIXING: After the soil and stabilization materials have been satisfactorily mixed, additions of water shall be made in the final mixing operations to complete the stabilization process. The method of mixing shall be an approved procedure utilizing a traveling mixing plant, which demonstrates uniform dispersion of stabilization material and water throughout the soil materials. The quantity of water necessary for the final mixing operations will vary with the nature of the materials normally 1 to 3 percentage points above the optimum moisture content of the compacted modified soil. Sufficient water in any case shall be added in the final mixing process to insure chemical action between the stabilization material and the soil. To insure proper moisture and density control, the contractor shall employ a qualified technician with a nuclear density gauge to confirm the moisture content of the sub-grade during the final mixing process. All clods (exclusive of aggregate) shall be reduced in size by mixing until the soil-cement kiln dust mixture meets the following size requirements when tested with laboratory sieves:

SIEVE SIZE: PERCENT PASSING

1 ½ inch 100 for lime, fly ash or cement kiln dust 34 inch 50 minimum for fly ash or cement kiln dust

#4 50 minimum for lime

#### **COMPACTION:**

Compaction of the stabilized base shall be performed immediately after final mixing, where in the compaction operation shall be a continuation of the final mixing operation. The sub-grade shall be compacted without delay and before any applicable loss of mixing moisture occurs. Mixing and compaction operations shall be performed in such a manner that the mixture will be compacted within plus 3 percentage points or minus 1-percentage points of optimum moisture content. However, during the course of construction, changes or adjustments in the specified moisture requirements to meet field conditions may be authorized by the engineer. Compaction shall continue until the entire depth of the mixture is uniformly compacted to not less than 95% of standard proctor density. The rate of operation and the number of rollers shall be sufficient to uniformly compact the section of roadway being processed within 3 hours of final mixing for fly ash or kiln dust.

The material shall be continually sprinkled and rolled. All irregularities, depressions or weak spots which develop shall be corrected immediately by scarifying the area affected, adding or removing material as required and reshaping and re-compacting by sprinkling and rolling.

In addition to the requirements specified for density, the full depth of the material shown on the plans shall be uniformly compacted to the extent necessary to remain firm and stable under construction equipment. After each section is completed, density tests as necessary will be made by the Engineer for acceptance. If the material fails to meet the density requirements, it shall be reworked as necessary to meet these requirements. Throughout this entire operation the shape of the base course shall be maintained and the surface upon completion shall be smooth and in conformity with the typical section shown on the plans and to the established lines and grades. Should the material, due to any reason or cause, lose the required stability, density or finish before the next course is placed of the work accepted; it shall be reworked and refinished at the sole expense of the Contractor.

In areas designated by the Engineer as excessive rock areas, it is the intent that compaction be in substantial compliance with these specifications. However, it is recognized that in some instances the mixture may not be uniform and some variation is possible in both the target density and optimum moisture. In the event the in-place density tests are not practical due to varying amounts of



## RETURN ONLY THE PAGES THAT YOU HAVE BID ON

**BID PROPOSAL** 

DATE:
NAME OF FIRM:
BIDDER AGREES TO COMPLY WITH ALL TERMS AND CONDITIONS OF BID
aggregate in the stabilization mixture, the Engineer may waive the density and moisture content requirements, and approve the subgrade compaction by visual observation with a approved test roller that has a minimum loaded weight of 25 tons.
FINISHING AND CURING: After the final layer of the modified sub grade has been compacted, it shall be brought within reasonable compliance to the lines, grades and typical sections. The completed section shall then be finished with a suitable roller sufficiently light to prevent hair cracking. The modified materials shall be maintained at a moisture content satisfactory for proper curing by sprinkling for a period of 14 days or until a prime, seal, or succeeding course is placed, whichever occurs first.
SURFACE TOLERANCE: The finished surface tolerance shall be in conformity with Section 301 (ODOT Standard Specifications, 1988 Edition).
METHOD OF MEASUREMENT:  (a) Cement Kiln Dust will be measured by the ton.  (b) Modified sub-grade will be measured by the square yards of sub-grade modification completed in place.  (c) Water will not be measured for payment.
BASIS OF PAYMENT: Accepted quantities for modified sub-grade measured as provided above, will be paid for at the contract unipprice for:  (d) Cement Kiln Dust TON  (e) Sub-grade Modification SQ. YARD
which shall be full compensation for furnishing all materials, equipment, labor and incidentals to complete the work as specified Payment for quick lime shall be based upon a 90 percent available lime index by rapid sugar method, calculated as percent CaO by weight. Payment for hydrated lime shall be based upon a 90 percent available lime index, by rapid sugar method, calculated as percent Ca(OH)2 by weight. When the available lime index percentage falls below 90 percent, payment will be made at an adjusted price. The adjusted price shall be reduced at the rate of one percent of the contract unit bid price for lime and for each percent, or fraction thereof, from 90.0 percent down to and including an available lime index of 80.0 percent. When the available lime index falls below 80.0 percent for the type of lime used, the contractor shall add a sufficient quantity of additional lime of the same type to bring the total amount to the required 90.0 percent of the available lime index at no additional cost to the department.
Bidder agrees to furnish and deliver the materials called for in bid specifications at the various locations and Districts listed above for the unit prices indicated. Delivery will be in truckload lots.
BITUMINOUS SEAL COAT: MATERIAL APPLIED AND FURNISHED PER MILE: 18' ROADWAY 20' ROADWAY 22' ROADWAY
SPECIFICATIONS: Seal Coat to be applied at the minimum rate of 0.05, to a maximum of 0.10 gallons of residual per square yard of surface area The residual per square yard will be determined by the COUNTY by the surface condition. Seal coat will be capable of enhancing the existing bituminous chip materials as listed below:  a) Penetration increases a minimum of three (3) points.
RESPECTFULLY SUBMITTED BY:



#### RETURN ONLY THE PAGES THAT YOU HAVE BID ON

DATE:	· •		ADIAN COUNT	Y	
NAME OF FIRM:			-		
			- 		
	DER AGREES T	O COMPLY V	VITH ALL TER	MS AND CO	ONDITIONS OF BID
(Continued) <u>SPECIFICATIONS</u>					
b) Absolute viscosity reduced	d a minimum of 20%	<b>⁄0.</b>			
c) Ductility increased a minir	mum of 30%.				
d) Material to increase high t					
<ul><li>e) Delay the aging of the exist</li><li>f) Improve low temperature f</li></ul>		terials.			
g) Improve adhesion to reduce					
h) Eliminate moisture penetra	ation.				
i) Penetrate into the first layer	r of chip to give mo	re flexibility.			
j) Decrease cracking and blee					
<ul><li>k) Eliminate hairline cracks (</li><li>l) The sealer will not track or</li></ul>					
			il material) before	and after the	Seal Coat application to determine the changed
	d price to include th	ne cost per square	yard to furnish and	apply the mat	erial. Material to be guaranteed for one (1) year
SPECIFICATION: Refer Minimum of 1/2 mile.	to current ODOT S	Specifications, Se	ction 402, Special	Bituminous S	Surface Treatment, 402.01 Special Description
BLEED CONTROL EMUL	SION: MATERIAL MATERIAI	L APPLIED PER ( L PER GALLON	GALLON IN PLAC	CE:\$ \$	
SPRAVING FOR WEE	DS FOR ALL	COUNTY RIII	ILDINGS: (To	include Indi	cial Building, Courthouse, Yukon Health
Department and Sheriff's (	Office.) \$	per sq. vd.	(10	merade sadi	olar Banding, Coarthouse, Takon House
			RE PAYMENT	IS MADE.	NO SUB-CONTRACTING WILL BE
ALLOWED.					
BILLS WILL BE PRESE	ENTED AT TWO	WEEK INTE	RVALS-PAYME	ENT WILL I	BE MADE WITHIN 2 WEEKS.
FOOD FOR CANADIAN	N COUNTY JAI	L AND/OR CA	NADIAN COUN	ITY JUVEN	ILE JUSTICE DETENTION CENTER:
<b>JAIL LOCATION: 208</b>	W. ROGERS EI	RENO, OK / D	ETENTION CE	NTER: 7905	5 E. HWY. 66 EL RENO, OK
GROUND BEEF:	price per pound:	\$	: purchase for	jail and dete	ntion center.
CHICKEN LEGS:	price per pound:	<b>\$</b>	: purchase for	detention cer	nter only.
CHICKEN THIGHS:			: purchase for		
CHICKEN QUARTERS:		***************************************	: purchase for		nter only. DIAN COUNTY JUVENILE JUSTICE
CENTER. MEAT ORDI					
RENTAL OF EQUIPME	NT: See Terms				
COLUDMENT.	IID.	_	PRICE PER:	WEEK.	MONTH.
EQUIPMENT: Asphalt Reclaimer	<u>HP:</u>	WGT/YDS:	MODEL:	***EEK:	MONTH:
Aspirate Recianner				\$	\$ \$
				\$	\$
RESPECTFULLY SUBM	ITTED BY				



## RETURN ONLY THE PAGES THAT YOU HAVE BID ON

DATE:	*****						
NAME OF FIRM:							
BIDD (CONTINUED)	ER AGREES	S TO COMPLY W		MS AND CO	ONDITIONS	OF BID	
EQUIPMENT: Pulva Mixer	<u>HP:</u>	WGT/YDS:	MODEL:	<u>WEEK:</u> \$	<u>MONTH:</u> \$		
4000 Gal Water Truck				\$ \$ \$	\$ \$ \$		
Vibratory Smooth Drum Roller				\$ \$	\$ \$		
Vibratory Padfoot Roller				\$ \$ \$ \$	\$ \$ \$		
DISTRUBUTOR TRUCK (County to furnish oil)		With Operator Without Operato	\$ or\$	\$ \$ \$	\$ \$ \$		
TERMS AND CONDITION County will carry at its of maintenance intervals (other and undercarriage componing negligence or from vandalismake the equipment availated maintenance intervals inclured acceptate wear items in the Scheduled maintenance musure of all repairs due to abust recommended daily and we repairs and Vendor and Concondition as received, less recounty AND VENDOR OF COUNTY AND VENDOR OF COUNTY COMMISSION WILL BE INITIATED AND COUNTY AND COMMISSION AND COUNTY AND COMMISSION AND COUNTY COMMISSION AND COUNTY AND COUNTY AND COUNTY AND COUNTY AND COUNTY AND COUNTY COMMISSION AND COUNTY COUNTY AND COUNTY COUNTY COUNTY AND COUNTY AND COUNTY AND COUNTY AND COUNTY AND COUNTY AND COUNTY COUNTY AND COUNTY AND COUNTY AND COUNTY AND COUNTY COUNTY AND C	own expense or than daily a tents during to the county against to complete the event Counts to be performed, damage, not be the label of the county will determ to the county will be county to the county will be compared to the cou	general liability in and weekly for which term of the regrees to notify Vendete the required material of wear items, to wishes to perform and inspections of mine the locations or and tear. County DA SIGNED EQUEFORE THE REI	nsurance. Venoch the County is ntal. Other than dor when the ser aintenance. Venores and Vendor the equipment 50 service meter operation, far County will parand extent of sur will have no opt UIPMENT RENTAL PROCES	dor will per responsible replacemen vice meter in ador will per will furnish t maintenance hours or 6 w illure to replay such repairs. Co ion to purcha NTAL AGRI SS IS TO B	form the reg including re t due to dar dicates sched form the reg o the County after normal reeks use. Co ace wear ited ir costs. Ven County will re ase the equipr EEMENT Al	gular manuface placement of mage resulting duled maintenagular manuface all fluids, filte working hours ounty is responsion of the property of the equipment rented.	cturers scheduled wear items, tires g from County's ance is due and to turer's scheduled ers and s or on weekends. In sible for the cost m manufacturer's sible for all other oment in the same
RESPECTFULLY SUBMI	ITED BY						



#### RETURN ONLY THE PAGES THAT YOU HAVE BID ON

DATE:	CANA	DIANCOUNT
BID	DER AGREES TO COMPLY WI	TH ALL TERMS AND CONDITIONS OF BID
	<b>LORIDE:</b> Liquid Calcium Chlorion that the following specificat	de is to be delivered and installed in place at jobsite location ordered by ions:
Liquid Calcium Chloride specifications. 4,000 mini PRICE PER GALLON @ PRICE PER GALLON @	mum order load. 234%:	plution to meet or exceed ASTM D-98-87 and AASHTO M144-86
	mum % MgC1 solid furnished. 4,3	Minimum 31% MgC1 liquid solution. Unit price will be reduced for any 00 Minimum order load.
	ution, not requiring any mixing, ble s certification may be required to be	ending or dissolving. Delivery of product shall begin within 24 hours of turnished with each truckload.
<ol> <li>Vendor is to pro applying liquid C</li> <li>Application equiperation cac12 stabilization cac12 stabilizer</li> <li>If county is apply in one pass.</li> <li>County will present the determined a</li> </ol>	aC12 stabilizer.  ment shall be a pressurized spray on agent. Application equipment shat an application rate of 0.25 – 0.35 ing CaC1 with a re-claimer, vendor pare the roadbed prior to contrat the jobsite by the project superstant.	unit specifically designed for road treatment and application of liquid hall be able to spray up to 24 ft. wide in one pass and capable of applying gallon per square yard per single pass.  will apply CaC1 as a topcoat at a rate of 0.25 per gallon per square yard ctor applying CaC12. Application rate, width of application will
Canadian County, no app charges. No surcharges w 1. Dry Calcium Chloride	ill be allowed.	purchase of the dry product. The bid price shall include the delivery  \$ \$ \$ \$ \$ \$ \$
	OF LIQUID CALCIUM CHLO	\$ DRIDE, LIQUID MAGNESIUM CHLORIDE, DRY CALCIUM LLL BEGIN WITHIN 24 HOURS OF PLACING ORDER.
RESPECTFULLY SUBM	ITTED BY:	
	201 N. Choctaw A	Avenue, El Reno, OK 73036



### RETURN ONLY THE PAGES THAT YOU HAVE BID ON

BIDDER AGREES TO CO	MPLY WITH ALL TI	ERMS AND CONDIT
<u> DIL AND CHIPPING</u> as per ODOT 2009 Standard Specifications Sec	20'ROADWAY	22'ROADWAY
(price per mile)		BITUMINOUS
) Asphalt chipping complete Vendor will		
furnish everything. Include rolling & prime		
coat. ) Vendor will furnish equipment and labor,		
including rolling. County will furnish oil		
and chips.		
) County to furnish oil, Vendor to furnish		
all other.		
Court to Court III Walls		
) County to furnish chips, Vendor to furnish all other.		
ENDOR TO FURNISH TRAFFIC CONTROL	L	
OIL AND CHIPPING	20'ROADWAY	22'ROADWAY
as per ODOT 2009 Standard Specifications Sec	tion 403 – See Attachn	nent Exhibit "B")
price per mile)	DOUBLE 1	BITUMINOUS
) Asphalt chipping complete Vendor will		
furnish everything. Include rolling & prime		<del> </del>
coat.	-41 402 - G A44 - I	4 E 1 1 1 4 4 E 100
as per ODOT 2009 Standard Specifications Sec		
as per ODOT 2009 Standard Specifications Seconice per mile)		ment Exhibit "B") BLE BITUMINOUS
as per ODOT 2009 Standard Specifications Seconice per mile)  Vendor will furnish equipment and labor,		
as per ODOT 2009 Standard Specifications Seconice per mile)  Vendor will furnish equipment and labor, including rolling. County will furnish oil		
as per ODOT 2009 Standard Specifications Seconice per mile)  Vendor will furnish equipment and labor,		
as per ODOT 2009 Standard Specifications Secrice per mile)  Vendor will furnish equipment and labor, including rolling. County will furnish oil and chips.  County to furnish oil, Vendor to furnish		
as per ODOT 2009 Standard Specifications Seconice per mile)  Vendor will furnish equipment and labor, including rolling. County will furnish oil		
as per ODOT 2009 Standard Specifications Secrice per mile)  Vendor will furnish equipment and labor, including rolling. County will furnish oil and chips.  County to furnish oil, Vendor to furnish all other.		
as per ODOT 2009 Standard Specifications Secrice per mile)  Vendor will furnish equipment and labor, including rolling. County will furnish oil and chips.  County to furnish oil, Vendor to furnish all other.  County to furnish chips, Vendor to furnish all other	DOU	
as per ODOT 2009 Standard Specifications Securice per mile)  Vendor will furnish equipment and labor, including rolling. County will furnish oil and chips.  County to furnish oil, Vendor to furnish all other.  County to furnish chips, Vendor to furnish all other	DOU	
as per ODOT 2009 Standard Specifications Secrice per mile)  Vendor will furnish equipment and labor, including rolling. County will furnish oil and chips.  County to furnish oil, Vendor to furnish all other.  County to furnish chips, Vendor to	DOU	



### RETURN ONLY THE PAGES THAT YOU HAVE BID ON

DATE:			
NAME OF FIRM:			
	AGREES TO COMPLY	WITH ALL TERMS AND	CONDITIONS OF BID
(Continued)			
OIL AND CHIPPING		20'ROADWAY	22'ROADWAY
(as per ODOT 2009 Standard (price per mile)	Specifications Section 403	– See Attachment Exhibit DOUBLE BITUN	
1) To furnish equipment, mater			
Control for <u>prime coat</u> , price			
	MC-3	80Oil:	
2) To furnish equipment, mater			
for SS-1 Fog Seal – 70/30	mix @.10 gal sq. yd.		
price per mile.	9 9 .,		
3) To furnish equipment, mater	ials and traffic control		
for CQS-1F (Quick setting, h			
content.)	ligher on residual		
•	EELC COMEDOI		
VENDOR TO FURNISH TRA	FFIC CONTROL		
conditions. Place of delivery shordered by the County can resul Specifications "Section 700 Mashowing material meets specifications".  ASPHALTIC MATERIALS-FAC 7.5	all be listed on the invoice. It in loss of time charge affaterials" Current Edition. ations. OB CANADIAN COUNTY	Failure to the supplier to dected by the County on the Materials delivered shall	
AC			
MC 30	DEMURRAGE CHAR	GE	<u> </u>
MC 800			
MC 3000			
SS 1			
SS 1H	PUMP CHARGE		
CRS 2			
MS 2	APPLICATION OF MA	ATERIALS:	
CMS 1	PER GALLON \$		
CRS2+			
AEP			
HOT MIX ASPHALT S-4 – FO	OR	PLANT, SPECIFY LOAD	D MINIMIM
PRICE PER TON:	(LOCATION)	_i Emili, Si Een i Bon	D IVILITATIVE CIVI
TRICE LER TON.	5 TONS OR LESS	MORE THAN 5 TONS	
COLD LAY	5 TONS OR LESS	MORE MAN 9 TONS	
COLD LAT			
DECRECATELL LA CLUS AMORDO	D. D.V.		
RESPECTFULLY SUBMITTED	JRI;		
	201 N. Choctay	w Avenue, El Reno, OK 73	036

### RETURN ONLY THE PAGES THAT YOU HAVE BID ON

BID PROPOSAL

IAME OF E							
AIVIE OF F	IRM:			<del></del>			
	BIDD	ER AGREES TO	COMPL	LY WITH AI	LL TERMS	AND CONDITIO	ONS OF BID
OT MIX E						00 to 1400 TONS:	
	S3 (64-22)	S4 (70-28)	*S3 (6			obs that require b	oth mix designs
L RENO			*		=		
UKON			*	+			
ALUMET			*	+			
IAPLE			*	+			
VALNUT			*		=_		
IEDMONT		<u></u>	*		=		
MUSTANG			•				
OKARCHE	·		*	+			
GEARY			*	+ +			
IDAIN I			·	т			
	S3 (64-22)	S4 (70-28)				OVER 1400 TON jobs that require	<u>NS:</u> both mix designs
L RENO			*		=_		
UKON ALUMET			*		=	<del></del>	
MAPLE			*			<del></del>	
			*	'			
VAINIIT			*				
						<u> </u>	
IEDMONT			*	+	=		
PIEDMONT MUSTANG	Y		*	++			
IEDMONT MUSTANG INION CIT	Y			+	=_		
IEDMONT MUSTANG INION CIT OKARCHE	Y		*		=		
PIEDMONT MUSTANG JINION CITY DKARCHE GEARY ALL ROCI Tack Coat	TO COMPL before applica	LY WITH ODOT	* * * SPECIF	+ + + ICATIONS '	= = = = = = = = = = = = = = = = = = =	700 MATERIAL	S" CURRENT EDITIO
PIEDMONT MUSTANG JINION CITY OKARCHE GEARY ALL ROCI Tack Coat	K TO COMPI before applica K: price per t	LY WITH ODOT	* * * SPECIF	+ + + ICATIONS '	= = = = = = = = = = = = = = = = = = =	 700 MATERIAL	S" CURRENT EDITIO
IEDMONT MUSTANG INION CITY OKARCHE GEARY  ALL ROCI Tack Coat  ROAD ROC  3/8" #2 cove	K TO COMPI before applica K: price per t	LY WITH ODOT	* * * SPECIF	+ + + ICATIONS '	= = = = = = = = = = = = = = = = = = =	700 MATERIAL	S" CURRENT EDITIO
PIEDMONT MUSTANG JNION CITY OKARCHE GEARY  ALL ROCI Tack Coat  ROAD ROC  3/8" #2 cove 5/8" #3 cove	K TO COMPI before applica K: price per t Fer	LY WITH ODOT ation to be included to	* * * * * * * * * * * * * * * * * * *	+ + + ICATIONS '	= = = = = = = = = = = = = = = = = = =	700 MATERIAL	S" CURRENT EDITIO
PIEDMONT MUSTANG JINION CITY DKARCHE GEARY  ALL ROCI Tack Coat  ROAD ROC  3/8" #2 cove 5/8" #3 cove 5/8" #3 was	K TO COMPI before applica K: price per t Fer er er hed cover	LY WITH ODOT	* * * * * * * * * * * * * * * * * * *	+ + + ICATIONS '	= = = = = = = = = = = = = = = = = = =	700 MATERIAL	S" CURRENT EDITIO
OKARCHE GEARY ALL ROCI Tack Coat	K TO COMPI before applica K: price per t Fer er er hed cover	LY WITH ODOT ation to be included to	* * * * * * * * * * * * * * * * * * *	+ + + ICATIONS '	= = = = = = = = = = = = = = = = = = =	700 MATERIAL	S" CURRENT EDITIO



## RETURN ONLY THE PAGES THAT YOU HAVE BID ON BID PROPOSAL

**CANADIAN COUNTY** 

DATE: NAME OF FIRM: BIDDER AGREES TO COMPLY WITH ALL TERMS AND CONDITIONS OF BID (Continued) **ROAD ROCK: price per ton:** (please specify pit) (OTHER) FOB RICHARD SPUR FOB CYRIL: FOB \_\_\_\_ 1/4" shot \*3/4" #1 cover ½" crusher run 3/4" crusher run 1 1/2" crusher run Surge Rock 4";6";8" 3/8" screenings 1" crusher run 1/4" granite chips 3/8" granite chips 1/2" #57 1/2" Class B 1" #67 Aggregate Base Type "A" Rock Rip Rap ON ALL SURGE ROCK, PLEASE SPECIFY 4", 6", 8". PROCESSED GYP-PRICE PER TON: (OTHER PIT) FOB WEATHERFORD FOB SOUTHARD FOB 1/2" crusher run 3/4" crusher run 1 ½" crusher run 2" clean 3/4" clean 6" surge Screenings Pit run **ROCK PICKED UP BY THE COUNTY FROM** ROCK PICKED UP BY THE COUNTY FROM PLANT IN YUKON: PRICE PER TON: PLANT IN HYDRO: PRICE PER TON: \*3/8" # 2 cover \*3/8" #2 cover 5/8" #3 cover \*5/8" # 3 cover \*5/8" # 3 washed cover 1/2" #57 (A) \*3/8" # 2 washed cover \_\_\_\_\_ 1/2" #57 (B) 1/4" shot 3/4" #1 cover 1/2" crusher run \* 3/4" # 1 cover RESPECTFULLY SUBMITTED BY:



# RETURN ONLY THE PAGES THAT YOU HAVE BID ON BID PROPOSAL

DATE:	CANADIAN COUNTY
NAME OF FIRM:	
BIDDER AGREES TO COM	PLY WITH ALL TERMS AND CONDITIONS OF BID
(Continued)	
<b>ROCK PICKED UP BY THE COUNTY FROM</b>	ROCK PICKED UP BY THE COUNTY FROM
PLANT IN YUKON: PRICE PER TON:	PLANT IN HYDRO: PRICE PER TON:
1" #67	½" crusher run
2 1/2" crusher run	1 ½" crusher run
3/8" screenings	2 ½" crusher run
1 ½" crusher run	Surge Rock 4", 6" 8"
4" surge rock	3/8" screenings
1" crusher run	1" crusher run
*3/8" #2 washed cover 3/8" rinsed shot	1/4" granite chips
2/8" granite ching	3/8" granite chips 1/2" # 57
1/40	½" Class B
Rip Rap	1" # 67
	Rip Rap
PROCESSED SHALE: PRICE/TON:	
Price per ton if loaded by Vendor:	
\$	
Price per ton if loaded by County: \$	
PLEASE SPECIFY LOCATION:	
accordance with Oklahoma Department of Tran locations to be determined in Canadian County. with the Oklahoma Standard Specifications for	Striping, four inches in width, white and yellow paint, or thermo plastic in sportation specifications, and in conformity with the dimensions and the All materials and work performed on this contract shall be in accordance or Highway Construction, Latest Edition, including applicable Special Uniform Traffic Control Devices, AASHTOM249 (latest edition).
Contractor will furnish all necessary equipment, I insurance for safety; and prevent any liability aga inspections by Canadian County.	abor and materials, along with all warning signs, flag persons, and liability inst Canadian County while work is in progress. All work will be subject to
Water Base Paint cents per ft.	Epoxy Paintcents per ft.
RESPECTFULLY SUBMITTED BY:	
201 N. Cl	hoctaw Avenue, El Reno, OK 73036



Date Issued: Bid Number: November 12, 2013 SIX MONTH BIDS

Closing Date:

December 6, 2013 at 4:00pm

PO Box 458, 201 N. Choctaw Ave., El Reno, OK 73036

Opening Date:

December 9, 2013 at 9:30am

Commissioner's Meeting Room, 201 N. Choctaw Ave., El Reno, OK 73036

~ AFFIDAVIT~ Six Month Bids

State of Oklahoma ) County of Canadian) §

1, Sherry Murray, Purchasing Agent, in and for said County and State, do hereby certify that "Invitations to Bid" were sent to the following:

Advanced Workzone Services LLC

PO Box 1569

Muskogee, OK 74402-1569

Asphalt Producers Inc

105 NE 44th

Oklahoma City, OK 73105

BCM Oklahoma LLC **Boral Aggregates** 

PO Box 850450

Yukon, OK 73085

Brad's Lawn Service 1119 Sunset Drive

El Reno, OK 73036

BT Exp. Global Services

Attn: Lance Wells 204 N Loomis Road

Weatherford, OK 73096

Coffeyville Resources Refining &

Marketing LLC 1207 Sovereign Row

Oklahoma City, OK 73108

Dolese Bros Co

PO Box 677

Oklahoma City, OK 73101-0677

Farmers Supply & Transportation Co

PO Box 443

Cheyenne, OK 73628

6003 Sunderland Drive

Colleyville, TX 76034

Goldman Global Group

Attn: John L Hawkins

Irving, TX 75062

Asphalt & Fuel Supply LLC

4200 E Skelly Drive, Suite 600

Tulsa, OK 74135-3210

Atlas Asphalt Products Inc

Attn: Tyle

PO Box 75727

Oklahoma City, OK 73147

Beachlers IGA 210 E Elm

El Reno, OK 73036

Breshears Trucking Inc

11001 Ranch Road Mustang, OK 73064

C.L. Boyd

PO Box 26427 Oklahoma City, OK 73126

Dale Brown Inc

PO Box 1748

Ardmore, OK 73402

ePlan

4115 South Providence, Suite 105

Columbia, MO 65203

Ferguson Waterworks

2220 Southeast 18th Street Oklahoma City, OK 73129-8355

Leigh Hanson

Hanson Aggregates WRP Inc

8505 Freeport Pkwy, Suite 500

Asphalt & Fuel Supply 11282 Hemlock Street Overland Park, KS 66210

Atlas Paving Co Attn: Tyle

PO Box 75727

Oklahoma City, OK 73147

Bid News Construction project@bidnews.com

Bridge & Highway Materials Inc

**PO Box 228** 

Enid, OK 73702

Calumet Steel & Surplus LLC

14040 122<sup>nd</sup> Street NW

Calumet, OK 73014

Diamond Gypsum PO Box 622

Okarche, OK 73762

Ergon Asphalt & Emulsions Inc

Attn: Johnny

9301 SW Koch Street

Lawton, OK 73505

Francis Tuttle Vo-Tech Center

Attn: Bid Assistance – Judy Robbins

12777 N Rockwell

Oklahoma City, OK 73142

Haskell Lemon Construction Co

PO Box 75608

Oklahoma City, OK 73147



Hoskins Gypsum Co LLC PO Box 243 Longdale, OK 73755

Joe Brown Co Inc PO Box 1669 Ardmore, OK 73402

Kirby Smith Machinery PO Box 270300 Oklahoma City, OK 73037

Martin Marietta Materials 229 N Service Road, Suite 1 Moore, OK 73160

Norman Supply PO Box 1079 Oklahoma City, OK 73101

Railroad Yard PO Box 2283 Stillwater, OK 74076

Schwarz Ready Mix PO Box 850450 Yukon, OK 73085

Sorco Products Inc PO Box 1230 Cushing, OK 74023

T & C Asphalt Materials LLC 406 N Blaine Avenue Chandler, OK 74834

Turf Care and Beyond PO Box 506 El Reno, OK 73036

Walkenhorst's 540 Technology Way Napa, CA 94558

Wood & Sons Paving Inc 200 East I-35 Service Road Edmond, OK 73034

Hydro Quarry LLC 7022 CR 1060 Hydro, OK 73048

Just Knock Ground Services Attn: Johnny Jones 245 N El Reno Ave El Reno, OK 73036

Kris and Shelly Johnson 4435 Hefner Road NE El Reno, OK 73036

Midstate Traffic Control Inc 12501 N Santa Fe Avenue Oklahoma City, OK 73114

Oklahoma Contractor's Supply LLC PO Box 82125 Oklahoma City, OK 73148

Reed Construction Data 30 Technology Pkwy South, Suite 100

Scotwood Industries Inc 12980 Metcalf Avenue, Suite 240 Overland Park, KS 66213

Stromberg Lumber Company Attn: Hale Stromberg PO Box 1412 Ardmore, OK 73402

Norcross, GA 30092

Time Striping Inc PO Box 1236 Van Buren, AR 72957

Vance Brothers Inc Attn: Greg Fuller 9306 E 11<sup>th</sup> Street, Suite A Tulsa, OK 74112

Warren Power & Machinery Inc 4501 W Reno Oklahoma City, OK 73127

Wright Asphalt Products Co Attn: Lance Fischer 4609 W Meadowlark Battlefield, MO 65619

Interstate Gypsum PO Box 720112 Oklahoma City, OK 73172

K&O Construction & Supply Co

PO Box 1845 Enid, OK 73702

Logan County Asphalt 2905 Commerce Blvd Guthrie, OK 73044

Myco Construction Corporation PO Box 750 Wheatland, OK 73097

Online Data Services 8460 Holcomb Bridge Road, Suite 100 Alpharetta, GA 30322

Schwarz Paving Co Inc 8251 W Reno Oklahoma City, OK 73127

Silver Star Construction Co Inc 2401 S Broadway Moore, OK 73160

Sunbelt Equipment & Supply 103147 S Highway 18 Meeker, OK 74855

TJ Campbell Construction Co PO Box 15129 Oklahoma City, OK 73155

VanKeppel's 8233 W Reno Oklahoma City, OK 73127

Western Aggregates LLC 8251 West Reno Avenue Oklahoma City, OK 73127

Yellowhouse Machinery Co 1300 West Chestnut Ave Enid, OK 73073

Witness my hand and seal this 12th day of November, 2013.

(SEAL)

Sherry Murray, Parchasing Agent

If you have any questions or need additional information, please contact: Sherry Murray, Purchasing Agent, 405.295.6125 or 405.422.2441